

Package: leaflet.providers (via r-universe)

September 11, 2024

Type Package

Title Leaflet Providers

Version 2.0.0.9000

Description Contains third-party map tile provider information from 'Leaflet.js', <https://github.com/leaflet-extras/leaflet-providers>, to be used with the 'leaflet' R package. Additionally, 'leaflet.providers' enables users to retrieve up-to-date provider information between package updates.

License BSD_2_clause + file LICENSE

URL <https://rstudio.github.io/leaflet.providers/>,
<https://github.com/rstudio/leaflet.providers>

BugReports <https://github.com/rstudio/leaflet.providers/issues>

Depends R (>= 2.10)

Imports htmltools

Suggests jsonlite, testthat (>= 3.0.0), V8

Config/Needs/website tidyverse/tidytemplate

Config/testthat/edition 3

Encoding UTF-8

Language en-US

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Collate 'providers_data.R' 'get_current_providers.R'
'leaflet.providers-package.R' 'zzz.R'

Repository <https://rstudio.r-universe.dev>

RemoteUrl <https://github.com/rstudio/leaflet.providers>

RemoteRef HEAD

RemoteSha 526ee9a426f60ec709ece0b28d360f45f925942e

Contents

get_providers	2
providers_default	3
providers_loaded	3
use_providers	4
Index	5

get_providers	<i>Fetch leaflet providers from Leaflet.js.</i>
---------------	---

Description

Fetch leaflet providers from Leaflet.js.

Usage

get_providers(version_num = NULL)

Arguments

version_num	Version number with which to update leaflet providers. If NULL, fetches most recent version.
-------------	--

Value

leaflet_providers object containing providers_version_num, providers_data, providers_details_data, src

Examples

```
if (
  interactive() &&
  requireNamespace("V8", quietly = TRUE) &&
  requireNamespace("jsonlite", quietly = TRUE)
) {
  get_providers()
  get_providers("1.8.0")
}
```

providers_default	<i>Return default providers, providers_details, version, and HTML Dependency.</i>
-------------------	---

Description

Return default providers, providers_details, version, and HTML Dependency.

Usage

```
providers_default()
```

Value

leaflet_providers object containing providers_version_num, providers, providers_details, and src

Examples

```
str(providers_default(), max = 3, list.len = 4)
```

providers_loaded	<i>Return currently loaded providers, providers_details, version, and HTML Dependency.</i>
------------------	--

Description

Return currently loaded providers, providers_details, version, and HTML Dependency.

Usage

```
providers_loaded()
```

Value

leaflet_providers object containing providers_version_num, providers, providers_details, and src

Examples

```
str(providers_loaded(), max = 3, list.len = 4)
```

use_providers	<i>Use custom tile provider</i>
---------------	---------------------------------

Description

Use a custom leaflet_providers object, e.g. providers data fetched with [get_providers](#), with the leaflet package.

Usage

```
use_providers(providers_info = NULL)
```

Arguments

`providers_info` A custom leaflet_providers object. If NULL, uses default providers.

Examples

```
if (require("V8") && require("jsonlite")) {  
  # Set providers to latest providers  
  use_providers(get_providers())  
  
  # Set providers to a custom providers object (specific version number)  
  use_providers(get_providers("1.4.0"))  
  use_providers("1.4.0")  
}
```

Index

`get_providers`, [2](#), [4](#)

`providers_default`, [3](#)

`providers_loaded`, [3](#)

`use_providers`, [4](#)